

IN THE SPECIFICATION:

These replacement paragraphs are submitted to clarify the specification. Applicants submit that no new matter is injected into the application by way of the substitute paragraphs.

Please replace the paragraph beginning at page 9, line 16, with the following paragraph:

-- As indicated above, apparatus **10** comprises a set of tactile switching devices **TD₁ – TD₆**. Tactile switching devices **TD₁ – TD₆** are mounted at the frame for manipulation by a user of apparatus **10**. In the advantageous embodiment illustrated herein, apparatus **10** additionally comprises swing arms **SA₁** and **SA₂**. Two sets of three tactile switching devices, **TD₁ – TD₃** and **TD₄ – TD₆**, are respectively mounted to swing arms **SA₁** and **SA₂** in a generally linearly spaced-apart relation, for a total of six tactile switching devices **TD₁ – TD₆**. The sets of tactile switching devices **TD₁ – TD₃** and **TD₄ – TD₆** comprise corresponding sets of pushbuttons **PB₁ – PB₃** and **PB₄ – PB₆** for manipulation by the user, and pushbutton switches **SW₁ – SW₃** and **SW₄ – SW₆** (see Figures 6A – 8) that are ~~actuatable~~ actuatable in response to manipulation of respective pushbuttons **PB₁ – PB₃** and **PB₄ – PB₆**. Tactile switching devices **TD₁ – TD₆**, and their respective pushbuttons **PB₁ – PB₆** and pushbutton switches **SW₁ – SW₆** are described in more detail below.--